



673FS

DOUBLE PIN TYPE FORK POSITIONER WITH WELDED FORKS



This model guarantee a constant and synchronized movement of the forks, using differentiated cylinders. Thanks to the sliding on the pin, these attachments are perfect for heavy duties; Other varieties with forks of different sections and lengths, equipped with check valve for barrel grabbing can be produced on request. On every model a pressure limit valve is supplied as standard.

REFERENCE	ATTACHMENT CAPACITY P - Kg	LOAD CENTRE CC - mm	ISO 2328 FEM	CARRIAGE WIDTH A - mm	EXTERNAL HOOKS B - mm	OPENING RANGE		FORK WIDTH D - mm	THICKNESS S - mm	CENTER OF GRAVITY CG - mm	WEIGHT Q - Kg
						C MIN - mm	C MAX - mm				
18YFA2A0001	2500	500	II	980	750	360	930	120x40x1200	157	78	240
18YFA2A0002	2500	500	II	1040	750	360	990	120x40x1200	157	76	245
18YFA2A0003	2500	500	II	1100	750	360	1050	120x40x1200	157	74	250
18YFA2A0004	2500	500	II	1150	750	360	1100	120x40x1200	157	71	260
18YLL3A0001	5000	500	III	1150	880	400	1080	150x50x1200	192	265	440
18YLL3A0002	5000	500	III	1250	880	400	1180	150x50x1200	192	262	450
18YLL3A0003	5000	500	III	1350	1000	400	1280	150x50x1200	192	260	500
18YLL3A0004	5000	500	III	1560	1210	400	1490	150x50x1200	192	253	620
18YLL3A0005	5000	500	III	1660	1210	400	1590	150x50x1200	192	249	700
18YLM4A0004	5000	600	IV	1200	900	550	1110	150x60x1200	224	259	560
18YLM4A0005	5000	600	IV	1400	1100	550	1310	150x60x1200	224	256	620
18YR04A0001	8000	600	IV	1740	1450	550	1650	200x60x1200	224	248	730
18YR04A0002	8000	600	IV	1800	1500	550	1710	200x60x1200	224	247	760
18YR04A0003	8000	600	IV	2000	1700	550	1910	200x60x1200	224	243	820
18YR14A0001	8000	900	IV	2200	2150	550	2110	200x70x1200	234	240	880
18YR14A0002	8000	900	IV	2400	2150	550	2310	200x70x1200	234	237	900



Hydraulic functions required: 1.
Maximum working pressure: 80 bar.

The references indicated on table are relative to standard attachments.
For the position of hydraulic connection see detail below.

